

operation instruction

Executive Standard:GB14748



BABY STROLLER MODEL

Please read this manual carefully before apply, and save for future reference.

If you don't follow the directions, likely crisis to your child's safety

Standard configuration listing

★ Before installation and use, please check carefully whether the product damage and lack of parts, or sharp edge, if you have any loss and damage of components, please contact customer service for the first time. Please regularly check body, in order to ensure the service life on the local, please follow the correct use of this manual.



The installation steps show

★ The local must be assembled by adult, children are not allowed to fold, assemble, and remove the default. Expand or folding frame, must pay attention to safety, avoid hurt fingers. When installing parts, please make sure that installation in place.

1. Frame opening

Will push up the raise, on the local know hear a "click" sound, show that the frame has begun in place



- Local car seat or basket may not be placed in use by other models on the stroller frame.
- Default of designed for 0 ~ 36 months infant design and weight no more than 15 KGS.
- Sleeping basket state cushion thickness shall be used for more than 15 mm.
- Push the bearing will affect the stability of the on the local, to prevent vehicle rollover or out of control, may be pushing hang on any weight.
- Backrest store content bag biggest bearing is 0.8 KG, storage basket of maximal bearing 3 KGS, if beyond the bearing of manufacturer recommendations, may affect the stability of car body
- Crossover vehicle maximal bearing is 0.5 KGS
- The local maximum safe bearing is 15 KGS, one at a time can also take a baby, it is forbidden to other infants and young children by default at the same time
- The way to implement the time attention should be paid to traffic safety
- To prevent accidental cart to sell, need to use in the process of the wrist band
- On the stairs or the elevator must pay attention to safety when using, must first held the infant sleep basket or seat
- When children take care shall not leave
- Before using the cart to ensure all locking devices have been is locked
- When a cart change to ZuoDou mode, and sit back and seat pocket mode surface maximum Angle is less than 150 degrees, the cart is not suitable for children under 6 months of use
- Keep away from fire on the local, please willing to fire
- Execution standard: GB14748-2008.

Maintenance

- Wet dishcloth quickly scrub and dry quickly.
- Regularly check whether there is a screw loose, parts damaged or suture fracture, if necessary, please replace the damaged parts, tear open outfit, please according to the manual operation, so as not to cause unnecessary damage.

Other matters needing attention

- Placing heavy objects on top of the default is prohibited.
- It is prohibited to use other non-genuine spare parts or accessories
- To the dust and stains in general, it is suggested that use wet dishcloth quickly scrub and dry quickly
- Awnings seat cloth and cloth do not machine wash
- To avoid fabric surface damage, shall not be forcibly scrub cloth
- Will dry it after washing cloth in ventilated place, do not exposure



3. Folding stroller

Fingers will push rod locks up, at the same time, his hands pressed back again, can be folded to collect.

The closed locks on both sides of the push rod, pull up at the same time



Collect complete easily dragged



Hands pressed back

Security principle

★ Should be detailed read this manual carefully before using this product, according to the manual used correctly

- The local should be assembled by adult, forbidden folding, assembly, or remove the local children.
- In order to avoid accidents, the use of the car must determine the components installed in place.
- Expand or folding frame must pay attention to safety, avoid hurt fingers.
- Forbidden will default to use as a toy, it is strictly prohibited for children baby cart.
- When placing children in the car or the car hold out children should be enabled when braking device.
- Infants to prevent accidental fall and slide, must fasten your seat belt when using local car (crotch, waist and shoulder belt)
- Buckle ring could cause choking, do not use should be fastened when the local.
- In order to prevent infants and young children were injured, must pay attention to infants and young children in the process of adjusting the local action.
- When parking the local must be put on the brakes.
- Infants and young children can independent seated posture, you must stop using the basket.

2. Front wheel installation and removal

Lift the frame front foot tube, aim the front axle wheel mounting holes, fully inserted, another front wheel installed in the same way.



front wheel installation



front wheel finish installing



press this button to remove front wheel

NOTE: Before using the front wheel down with proper strength, to see if the front wheel installed

3. Rear wheel installation and removal

Before install the rear wheels to raise frame back foot tube, install the axle after fully inserted into the rear wheels, the same method to install another rear wheels



rear wheel installation



rear wheel finish installing



upper this button to remove rear wheel

NOTE: Before using the front wheel down with proper strength, to see if the front wheel installed

4. Canopy installation and removal

Aim the shutters on both sides of the black card a sleeping basket on both sides of the booth, push the bottom, then speak awnings and slept on the zipper pull basket.Awnings can also be removed.



Card prison awnings



Pull zipper



Finish installing



Remove canopy

5. The installation of the armrest

Aim the handrail armrest hole insert in turn. The armrest can be unilateral bilateral pull plug removal



6. The installation of seats disassembly and adjustment

Basket will sleep on both sides of the plug on the chassis seat slots at the same time, put down the seat, make on both sides of the plug can be inserted into the slot at the same time, will seat down and press until it has safety lock. his hands hold as the little square on both sides of the button at the same time, can remove the seat, both hands hold both sides round big keys to adjust the seat height



Hands hold down the button to turn the circle is big sleep basket can adjust the Angle



Both hands hold the little square button to remove the seat basket



Sleep will seat basket of adjustment to the appropriate view, buckle lock buckle fixed up

7. The use of seat belts and adjust

Infants to prevent accidental fall or slide, when using the default must buckle up law (crotch, waist and shoulder belt) method of use and regulation as shown in the figure below.



Open seat belts directly by the middle of the circle button, can bounce off



Belt plug as shown in figure directly into the can



Shoulder straps of disassembling as shown in figure into and sliding out

Function display

★ To avoid injury, infants and young children sat on the seat don't move or adjust the seat. At the bottom of the seat and sleeping basket state transform regulation by two safety clasp and a backrest adjustment lock. When want to transform into a seat, will fit two safety back to adjust the lock at the bottom of the QQ, make sure that there is no loosening, sleep to transform into a basket, please make the bottom two safety clasp and backrest adjustment lock all loose



The upper regulating lock



In the end safety clasp



Lower safety clasp

1. Rear wheel brake function

Step on brake pedal with the foot back, rear wheel brake can be realized, remove brake conversely



State of the brake



Lift its state of the brake

2. 6 kinds of position

Sleeping basket of seats can be adjusted to be removed, embedded in the frame is come up before and after the implementation two-way direction, seat sleeping basket Angle can be adjusted seat, back, lie three block



Seat forward lie



Horizontal forward



Seated forward